


Speedroller

Best basis for intensive use



NextGen
Industrial Doors

STRONG

XtraFast

A reliable basis for intensive use

Properties

- max. surface area (WxH) = 25 m², max. width (W) = 5,000 mm, max. height (H) = 5,000 mm
- max. wind load resistance class 2 according to EN 12424, or up to 7 Beaufort minimal (50 - 61 km/h)
- opening speed with standard Frequency Control: between 1.8 and 2.3 m/s, depending on dimensions
- closing speed approx. 0.5 m/s
- 1.2 mm thick door curtain in blue, black, white, grey, red, orange or yellow
- various window types available as an option
- designed as a fast inside door for larger doorways with average wind load • EN13241 compliant

Max. wind load resistance*

Up to 3,000 mm	Class 2
Up to 4,000 mm	Class 1
Up to 5,000 mm	Class 0

STRONG

The STRONG-XF is designed for high speed and intensive use. The opening speed of up to 2.3 m/s makes this door practical even for heavy traffic and large passages. Ideal for large production processes that run quickly and where breakdowns are not allowed to occur.

Dimensions	
max. width	5,000 mm
max. height	5,000 mm
max. surface area	25 m ²
required lateral space at the guides	170 mm
required lateral space at slip on drive	340 / 425mm*
required lateral space at drive for fitting	440 / 475 mm*
lateral space at side guide profiles	145 / 200 mm*
space above	430 / 480 mm*
Max wind load resistance*	
Up to 3,000 mm Cl. 2	Up to 4,000 mm Cl. 1
Up to 5,000 mm Cl. 0	

Components and construction

The SpeedRoller Strong-XF is a door without balance springs, consisting of an electrically driven door curtain rolled up on an aluminium roller above the opening. The door curtain is made of horizontal sections of extremely durable polyester-reinforced PVC. The sections are fitted with aluminium reinforcement profiles with integrated EndLocks, and can be equipped with various types of vision- or insect netting sections between approx. 1,000 and 2,000 mm height. The bottom of the door curtain has a solid HardEdge bottom beam, a flexible FlexEdge bottom beam is available as an option. U-shaped columns with sideseals ensure lateral guidance of the door curtain. The lateral guides are one unit combined with the bearing plates for secure fastening to the roller and drive.

Materials

The door columns are made of two hot dip galvanised steel profiles. The front covers are removable for fast and simple installation and maintenance. The horizontal roller is aluminium. The HardEdge bottom beam is aluminium, the optional FlexEdge bottom beam is sturdy but flexible and has a soft outer shell. The door curtain is a 1,2 mm thick PVC with a polyester reinforcement inlay.

Colour

The door curtain is available in the colours blue, black, white, grey, red, orange or yellow and provided with a vision section.

Drive

The drive consists of an electric motor with reduction unit. The roller is directly driven. Drive side available left or right (standard).

Technical details electric motor

- mains voltage **1,5 kW** with frequency control LNPE~230V/50Hz/16AT
- mains voltage **3,0 kW** with frequency control..... 3N~400V/50Hz/16AT
- degree of protection..... IP65
- consumed power..... max. 2 kW

Performance	
control box with frequency control (optional):	
max. opening speed	between 1.8 and 2.3 m/s depending on dimensions
max. closing speed	0.5 m/s

Protection

- the door can be manually opened in the case of a power loss
- electric motor with reduction unit and built-in roll-off safety
- light curtain up to 2,500 mm high

Structural provisions and connection

- a flat mounting frame and the necessary mounting space must be available
- exact installation dimensions in the Technical Datasheet
- within a radius of 500 mm of where the control unit will be positioned there must be a wall socket:
 - CEE-form red, 3N~400V/50Hz fused, slow operation 16 A
 - CEE-form blue, 1 x 230V fused, slow operation 16 A fitted with a circuit-breaker of at least 300 mA
- the control box usually is fitted on the drive side, at a height of approx. 1,500 mm from the floor
- with standard CEE-plug, the control box is IP54 compliant

Control and operation

The control unit has 3 buttons (open-stop-close) and a CEE plug, and regulates a multitude of functions such as:

- adjustable open time
- service and run mode
- 7-segment display for control of the various functions
- permanently open or permanently shut

Additional controls that can be connected to the control box are:

- push-button, pull switch, key-operated switch, photocell, radar, induction loop detection or radio control.
- Other forms of operation on request



Available controls:	TS971, TS981
---------------------	--------------

Extras¹

Control and operation

- additional controls as described above
- control box directly wired (control box IP65)
- main switch directly wired on the control box (IP65)
- door interlock control in combination with another door

Protection

- connection of traffic lights (red/green or red and green)
- warning light (orange or red)

Construction

- flexible 'FlexEdge' bottom beam
- windows made of mosquito netting
- stainless steel columns
- PVC, metal or stainless steel hood
- hood and PVC cover in customer-specified RAL colour

* Depending on the configuration ¹ subject to surcharge